


CLEVIS HANGER W/SHIELD

ELECTRO-GALVANIZED

Clevis Hangers with Shields are designed for suspension stationary insulated pipes.

Insulation protection shield is spot welded in place onto Electro-Galvanized Clevis Hanger. For clevis hanger data, see Technical Data Sheet titled 'Clevis Hanger / Plain finish, electro-galvanized finish, copper epoxy coating'. Note, part numbers on this sheet consist of the welded assembly of shield welded to clevis hanger.



Shield also available separately.

KEY BENEFITS

- Electro-Galvanized
- Shield is spot welded in place
- Shield prevents hanger from cutting through insulation

DIMENSIONAL DATA



TABLE 1: DIMENSIONAL DATA OF CLEVIS HANGER W/ SHIELD

TABLE 1: DIMENS	IONAL DATA OF CI	LEVIS HANGER W/				WITH WELDED SHIELD
WELDED ASSEMBLY SIZE*						
PIPE SIZE	THICKNESS OF PIPE INSULATION					
(in.)	1/2"	1"	1-1/2"	2"	2-1/2"	3"
1/2	1-1/2	2-1/2	3-1/2	5	6	7
3/4	2	3	3-1/2	5	6	7
1	2	3	4	5	6	7
1-1/4	2-1/2	3-1/2	4	5	6	7
1-1/2	2-1/2	3-1/2	5	6	7	8
2	3	4	5	6	7	8
2-1/2	3-1/2	5	6	7	8	10
3	4	5	6	7	8	10
3-1/2	5	6	7	8	10	10
4	5	6	7	8	10	10
5	6	7	8	10	10	12
6	7	8	10	10	12	12
8	10	10	12	12	14	16
10	12	12	14	16	16	18
12	14	16	16	18	18	20
14	16	16	18	18	20	20
16	18	18	20	20s	24	24

^{*}Size represents clevis hanger size needed to accommodate pipe, insulation, and shield. The size determined by this table should be used in the next table to find the corresponding part number.

www.allfasteners.com | Customer Service 888.859.6060

ORDERING INFORMATION

TABLE 2: ORDERING INFORMATION OF CLEVIS HANGER W/ SHIELD

STANDARD CLEVIS HANGER - WITH WELDED SHIELD					
PART #	SIZE	SHIELD LENGTH	QUANTITY / BOX		
6CHSGV0200	2"	12"	1 / Box		
6CHSGV0300	3"	12"	1 / Box		
6CHSGV0312	3-1/2"	12"	1 / Box		
6CHSGV0400	4"	12"	1 / Box		
6CHSGV0500	5"	18"	1 / Box		
6CHSGV0600	6"	18"	1 / Box		
6CHSGV0700	7"	24"	1 / Box		
6CHSGV0800	8"	24"	1 / Box		
6CHSGV1000	10"	24"	1 / Box		
6CHSGV1200	12"	24"	1 / Box		
6CHSGV1400	14"	24"	1 / Box		
6CHSGV1800	18"	24"	1 / Box		

TABLE 3: ORDERING INFORMATION OF INSULATION PROTECTION SHIELD

	TABLE 6. ORBERING IN CRIMATION OF INCOLATION FROM CRIMED						
STANDARD CLEVIS HANGER - WITH WELDED SHIELD							
PART #	SIZE	SHIELD I.D.	QUANTITY / BOX				
6IPSG0200H	2 x 12"	2-3/8"	1 / Box				
6IPSG0300H	3 x 12"	3-1/2"	1 / Box				
6IPSG0400H	4 x 12"	4-1/2"	1 / Box				
6IPSG0500H	5 x 18"	5-5/8"	1 / Box				
6IPSG0600H	6 x 18"	6-5/8"	1 / Box				

TABLE 4: ORDERING INFORMATION

MATERIAL	Carbon steel clevis hanger with pre-galvanized shield		
FINISH	Electro-galvanized		
SERVICES	Designed for the suspension of stationary insulated pipe lines. Insulation protection shield is spot welded to the clevis hanger.		
ORDERING	Specify part number		
NOTES	Upper locknut must be tightened securely to assure proper hanger performance.		